(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 29 December 2004 (29.12.2004)

PCT

(10) International Publication Number WO 2004/113715 A1

(51) International Patent Classification7: 55/02. 59/10

F02M 63/02,

(21) International Application Number:

PCT/GB2004/002578

(22) International Filing Date:

17 June 2004 (17.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 03253919.9

20 June 2003 (20.06.2003) EI

(71) Applicant (for all designated States except US): DELPHI TECHNOLOGIES INC. [US/US]; P.O. Box 5052, Troy, MI 48007 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): KNIGHT, Andrew [GB/GB]; The Old Vicarage, Rockness, Horsley, Stroud, Gloucestershire (GB). WILKIN, Adam [GB/GB]; 8, The

Hayes, Southam Road, Prestbury, Cheltenham, Gloucestershire (GB).

- (74) Agents: HOPLEY, Joanne, Selina et al., David Keltie Associates, Fleet Place House, 2 Fleet Place, London EC4M 7ET (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW:
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: FUEL SYSTEM



(57) Abstract: A fuel system for supplying pressurised fuel to a plurality of fuel injectors (14a-14f) comprises an accumulator assembly (16) having first and second accumulator volumes (18, 20) defined within a common accumulator housing (22), supply means (42) for supplying fuel at a supply pressure level to the first accumulator volume (18) and a plurality of unit pumps (10a-10f). Each unit pump is arranged to receive fuel at the supply pressure level from the first accumulator volume (18) and pressurises said fuel to an injectable pressure level for supply to the second accumulator volume (20). Each unit pump (10a-10f) includes a pumping plunger (50) for pressuring fuel within an associated pump chamber (52) and being integrated with the accumulator housing (22) so as to permit communication between the first accumulator volume (18) and the pump chamber (52) internally within the accumulator housing (22).

O 2004/113715 A1

WO 2004/113715 A1

SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,

GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.